

# Xerox® WorkCentre® 7830i/7835i/ 7845i/7855i Colour Multifunction Printer

The WorkCentre 7800i Series Colour Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com)



System Specifications	WorkCentre 7830i	WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i
<b>Speed</b> Colour / Black and white	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages
<b>Hard Drive / Processor / Memory</b>	Minimum 250 GB HDD / 1.2 GHz Dual-core / 2 GB system plus 1 GB page memory			
<b>Connectivity</b>	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct with Optional Xerox® USB Wireless Adapter			
<b>Controller Features</b>	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning			
<b>Optional Controller</b>	EFI™ Fiery® Network Server			
<b>Copy and Print</b>				
<b>Copy and Print Resolution</b>	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 2400 dpi			
<b>First-print-out Time</b> Colour / Black and white	As fast as 9 / 7.7 seconds		As fast as 7.5 / 6.4 seconds	As fast as 7.1 / 5.9 seconds
<b>Page Description Languages</b>	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)			
<b>Print Features</b>	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bidirectional Status, Scaling, Job Monitoring, Xerox® Colour By Words			
<b>Mobile Printing and Apps</b>	<b>Standard:</b> Apple® AirPrint™, Mopria Certified, QR Code App, Xerox App Gallery App, @PrintByXerox App; <b>Free Download:</b> Xerox® PrintBack, Xerox® Print Service Plug-in for Android, Mopria™ Print Service Plug-in for Android™, Xerox® Mobile Link App; <b>Optional:</b> Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service			
<b>Scan</b>				
<b>Standard Features</b>	<b>Destinations:</b> Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; <b>File Formats:</b> PDF, PDF/A, XPS, JPEG, TIFF; <b>Convenience Features:</b> Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A			
<b>Optional Features</b>	ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional			
<b>Fax</b>				
<b>Standard Features</b>	Internet Fax, Fax Build Job, Network Server Fax Enablement			
<b>Optional Features</b>	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)			
<b>Security</b>				
<b>Standard Features</b>	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions			
<b>Optional Features</b>	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software			
<b>Accounting</b>				
<b>Standard Features</b>	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement			
<b>Optional Features</b>	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®			
<b>Device Specifications</b>				
<b>Control Panel Languages</b>	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic			

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

Accessories				
<b>Optional</b>	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7830i/7835i only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (Recommended use with optional Work Surface) Smart Card Enablement Kit EFI™ Fiery® Network Server Walk up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit			
<b>Foreign Device Interface (FDI) (Optional)</b>	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers.			
Electrical Requirements				
<b>Europe</b>	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A			
<b>Power Consumption</b>	<b>WorkCentre 7830i</b>	<b>WorkCentre 7835i</b>	<b>WorkCentre 7845i</b>	<b>WorkCentre 7855i</b>
<b>Running (Average)</b>	643 watts	691 watts	764 watts	862 watts
<b>Standby Mode</b>	62 watts		95.9 watts	121 watts
<b>Low Power Mode</b>	59 watts		80.5 watts	94.6 watts
<b>Auto Off / Sleep mode</b>	4.8 watts (Default time to Sleep mode = 2 mins)		4.8 watts (Default time to Sleep mode = 2 mins)	
<b>Warm-up</b>	Time from power off to when services are displayed: WorkCentre 7830i/7835i: As fast as 161 seconds WorkCentre 7845i/7855i: As fast as 152 seconds			
<b>Low Power Recovery</b>	< 9 seconds			
Operating Environment				
<b>Required Temperature Range</b>	10° to 28°C			
<b>Required Relative Humidity</b>	15% to 85%			
<b>Sound Power Levels</b>				
Operating	6.5 LwAd (B)	6.5 LwAd (B)	6.6 LwAd (B)	6.8 LwAd (B)
Standby	3.5 LwAd (B)	3.4 LwAd (B)	3.6 LwAd (B)	3.6 LwAd (B)
<b>Sound Pressure Levels</b>				
Operating	54 LpAd (dBA)	54.3 LpAd (dBA)	55.7 LpAd (dBA)	55.8 LpAd (dBA)
Standby	16.5 LpAd (dBA)	16.5 LpAd (dBA)	18.5 LpAd (dBA)	18.5 LpAd (dBA)
<b>Dimensions and Weight</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>Base Configuration</b>	640 mm	699 mm	1,149.2 mm	151.9 kg
<b>With Integrated Office Finisher (7830i/7835i only)</b>	1,129 mm	699 mm	1,149 mm	158 kg
<b>With Office Finisher LX (with Booklet Maker)</b>	1,666 mm	709 mm	1,149 mm	183 kg
<b>With Professional Finisher</b>	1,922 mm	699 mm	1,149 mm	239 kg
<b>With Professional Finisher and High Capacity Feeder</b>	1,922 mm	699 mm	1,149 mm	268 kg
Certifications				
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® 2.0 EPEAT (United States) GOST NOM Apple® AirPrint™ 1.4 Certification Mopria™ Certified Wi-Fi Direct Certification Blue Angel ECOLOGO® CE Mark Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) Citrix® Certified WHQL IPv6 Ready Cerner MEDITECH SAP To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a>			

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

Paper Handling	WorkCentre 7830i	WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i
<b>Duplex Automatic Document Feeder</b>				
Capacity <sup>3</sup>	110 sheets		130 sheets (Single-pass DADF)	
Speed	up to 70 image per minute black and white and colour (simplex)		up to 80 images per minute black and white and colour (simplex) / up to 133 images per minute black and white and colour (duplex)	
Paper Sizes Sensed	A5 to A3			
Weights	60 to 128 gsm			
<b>Bypass Tray</b>				
Capacity <sup>3</sup>	100 sheets			
Sizes	Custom sizes: 89 x 98 mm to 320 x 483 mm			
Weights	60 to 300 gsm			
Types	Bond Card Stock, Card Stock Reloaded Custom Envelopes Glossy Card Stock, Glossy Card Stock Reloaded Heavyweight Card Stock, Heavyweight Card Stock Reloaded, Heavyweight Glossy Card Stock, Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight, Lightweight Card Stock, Lightweight Card Stock Reloaded, Lightweight Glossy Card Stock, Lightweight Glossy Card Stock Reloaded Plain, Plain Reloaded Preprinted Recycled Transparencies			
<b>4 x 520-sheet Tray Model - Total 2,180 sheets (Optional with WorkCentre 7830i/7835i only)</b>				
Capacity <sup>3</sup>	Trays 1-4: 520 sheets each			
Sizes	Tray 1: Custom Sizes from 140 x 182 mm to 297 x 432 mm Trays 2-4: Custom Sizes from 139.7 x 182 mm to 320 x 457.2 mm			
Weights	60 to 256 gsm			
Types	Bond Card Stock, Card Stock Reloaded Custom Glossy Card Stock, Glossy Card Stock Reloaded Heavyweight Card Stock, Heavyweight Card Stock Reloaded, Heavyweight Glossy Card Stock, Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight, Lightweight Card Stock, Lightweight Card Stock Reloaded, Lightweight Glossy Card Stock, Lightweight Glossy Card Stock Reloaded Plain, Plain Reloaded Preprinted Recycled Transparencies			
<b>High Capacity Tandem Tray Model - Total 3,140 sheets (Available with all configurations)</b>				
Capacity <sup>3</sup>	Tray 1: 520 sheets Tray 2: 520 sheets Tray 3: 867 sheets Tray 4: 1,133 sheets			
Sizes	Tray 1: Custom Sizes from 140 x 182 mm to 297 x 432 mm Tray 2: Custom Sizes from 140 x 182 mm to 320 x 457.2 mm Trays 3-4: Standard Sizes: A4			
Weights	60 to 256 gsm			
Types	Bond Card Stock Custom Glossy Card Stock Hole punched Labels Letterhead Lightweight Card Stock, Lightweight Glossy Card Stock Plain Preprinted			
<b>High Capacity Feeder (HCF) (Optional)</b>				
Capacity <sup>3</sup>	2000 sheets			
Sizes	Standard Sizes: A4 LEF			
Weights	60 to 256 gsm			

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

<b>Envelope Tray (Optional – Replaces Tray 1)</b>				
<b>Capacity<sup>3</sup></b>	Up to 60 envelopes			
<b>Sizes</b>	DL, C5, 6 x 9 in. Custom sizes: 98 x 148 mm to 162 x 241 mm			
<b>Weights</b>	75 to 90 gsm			
<b>Total Capacity</b>				
<b>Device Total Capacity<sup>3</sup></b>	5,140 sheets			
<b>Finishing</b>				
<b>Output Trays (Standard)</b>				
<b>Stacking Trays<sup>3</sup></b>	Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets			
<b>Integrated Office Finisher (Optional with 7830i/7835i)</b>				
<b>Stacking Tray</b>	500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3			
<b>Sizes</b>	89 x 98 mm to 297 x 432 mm			
<b>Weights</b>	60 to 256 gsm			
<b>Stapling</b>	Single Auto stapling: 50 sheets maximum: A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)			
<b>Office Finisher LX (Optional)</b>				
<b>Capacity<sup>3</sup></b>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4)			
<b>Sizes</b>	210 x 182 mm to 297 x 432 mm			
<b>Weights</b>	60 to 256 gsm			
<b>Multiposition Stapling</b>	50 sheets of 90 gsm			
<b>Hole Punch (Optional)</b>	2-4 Hole Punch			
<b>Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)</b>				
<b>Capacity<sup>3</sup></b>	40 booklets (2-15 sheets per booklet – 80 gsm or less)			
<b>Sizes</b>	A4 SEF B4 SEF A3 SEF			
<b>Saddle-stitch Stapling</b>	2-15 sheets / 8-60 page booklet 60 to 90 gsm			
<b>Score / Crease</b>	1-15 sheets / unstapled			
<b>Professional Finisher (Optional)</b>				
<b>Capacity<sup>3</sup></b>	<b>Top Tray:</b> 500 sheets of A4 unstapled  <b>Stacking Stapling Tray:</b> 1,500 sheets of A4 / A3 / SRA3 unstapled or 200 stapled sets of A4 or 100 stapled sets of A3 / SRA3			
<b>Sizes</b>	182 x 182 mm to 320.2 x 483 mm for stacking 203 x 182 mm to 297 x 432 mm for stapling			
<b>Weights</b>	60 to 220 gsm			
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported			
<b>Hole Punch (Standard)</b>	2-4 Hole Punch 4 Hole Swedish Punch (Optional)			
<b>Booklet Maker</b>	Saddle-stitch 2 to 15 sheets (14 sheets of 90 gsm or less plus 1 sheet of 169 gsm) Bi-fold up to 5 sheets A3, A4, SRA3 supported			
<b>Convenience Stapler (Optional - recommend use with optional Work Surface)</b>				
<b>Capacity<sup>3</sup></b>	50-sheet stapling 5,000 staples Requires a separate outlet			
<b>Copy</b>	<b>WorkCentre 7830i</b>	<b>WorkCentre 7835i</b>	<b>WorkCentre 7845i</b>	<b>WorkCentre 7855i</b>
<b>First-copy-out Time (A4-size, from Platen to Centre Tray) (Colour / Black and white)</b>	As fast as 8.4 seconds / As fast as 6.7 seconds	As fast as 8.2 seconds / As fast as 6.8 seconds	As fast as 7.5 seconds / As fast as 6.2 seconds	As fast as 7.1 seconds / As fast as 5.5 seconds

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

<b>Sides (input:output)</b>	1-1, 1-2, 2-2, 2-1			
<b>Quantity</b>	1 to 9,999			
<b>Resolution (max.)</b>	Up to 600 x 600 dpi			
<b>Reduction / Enlargement</b>	Variable zoom from 25% to 400% in 1% increments			
<b>Concurrency</b>	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)			
<b>Copy Features</b>	<ul style="list-style-type: none"> <li>Annotation and Bates™ stamping (with colour capability and font size adjustment)</li> <li>Authentication for Services (i.e. Colour Copy)</li> <li>Auto Paper Select</li> <li>Auto Reduction &amp; Enlargement to fit selected paper size</li> <li>Auto Tray Switching</li> <li>Automatic 2-sided/Duplex</li> <li>Booklet Creation</li> <li>Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)</li> <li>Collation</li> <li>Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)</li> <li>Dividers (blank)</li> <li>Edge Erase</li> <li>Features Help (Intuitive text and graphic descriptions)</li> <li>ID Card Copy</li> <li>Image Quality Adjustments</li> <li>Image Shift (with Auto Centre option)</li> <li>Invert Image (negative or mirror image)</li> <li>Large Job Interrupt</li> <li>Multi-up (up to 15 columns by 15 rows)</li> <li>Sample Set</li> <li>Save Job Settings</li> <li>Single Colour</li> <li>Stapling</li> <li>Transparencies</li> </ul>			
<b>Xerox® Copier Assistant®</b>	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit <a href="http://www.xerox.com">www.xerox.com</a>			
<b>Print</b>	<b>WorkCentre 7830i</b>	<b>WorkCentre 7835i</b>	<b>WorkCentre 7845i</b>	<b>WorkCentre 7855i</b>
<b>Print Resolution</b>	Up to 1200 x 2400 dpi			
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Sheet Enable / Disable</li> <li>Bidirectional Real-time Status</li> <li>Custom Colour Options (Colour By Words)</li> <li>Cover Selection</li> <li>Delay Print (specific time)</li> <li>User Permissions</li> <li>Image Options (Toner Saver, Resolution (Standard, Enhanced, High)</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Layout / Watermark</li> <li>N-up (up to 16 pages per sheet)</li> <li>Booklet layout</li> <li>Finishing</li> <li>Fit to new paper size</li> <li>Hold All Jobs</li> <li>Paper Selection by Attribute</li> <li>LAN Fax (requires optional Fax Kit)</li> <li>Sample Set</li> <li>Saved Job (colour jobs can be printed as monochrome)</li> <li>Secure Print with Timed Deletion</li> <li>Special Pages (exception page programming: covers, inserts, exception pages)</li> <li>Store and Recall Driver Settings</li> <li>Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)</li> <li>Two-sided Printing (as default)</li> </ul>			
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port on front panel</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, PS, XPS®, PCL</li> <li>Colour jobs can be printed as monochrome</li> </ul>			
<b>Operating Systems</b>	<ul style="list-style-type: none"> <li>Microsoft® Windows® XP SP3 (32- and 64-bit)</li> <li>Windows Server 2003 SP2 R2 (32- and 64-bit)</li> <li>Windows Server 2008 and R2 (32- and 64-bit)</li> <li>Windows Server 2012 and R2 (64-bit)</li> <li>Windows Vista SP2 (32- and 64-bit)</li> <li>Windows 7 (32- and 64-bit)</li> <li>Windows 8 (32- and 64-bit)</li> <li>Windows 8.1 (32- and 64-bit)</li> <li>Windows 10 (32- and 64-bit)</li> <li>Mac OS 10.8, 10.9, 10.10, 10.11</li> <li>Linux® Redhat® Fedora® Core 20 x86</li> <li>Ubuntu® 14.04 x64</li> <li>openSUSE® 13.1 x64</li> </ul>			

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / AirPrint™ IPv6 Secure FTP Most protocols not in use can be disabled			
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP			
<b>Fonts</b>	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts			
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.			
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.			
<b>Xerox® Pull Print Driver</b>	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.			
<b>Print Solutions</b>				
<b>Xerox® Mobile Print Cloud (Optional)</b>	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.			
<b>Xerox® Mobile Print Solution (Optional)</b>	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.			
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.			
<b>Xerox® Mobile Link App (Free at Google Play Store and Apple® App Store)</b>	The Xerox® Mobile Link App allows you to scan, fax and print from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.			
<b>Unified Address Book for Fax, Internet Fax, Email and Scan to...</b>				
<b>Features</b>	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.			
<b>Scan</b>	<b>WorkCentre 7830i</b>	<b>WorkCentre 7835i</b>	<b>WorkCentre 7845i</b>	<b>WorkCentre 7855i</b>
<b>Concurrency</b>	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)			
<b>Input Speed</b>	Scan at up to 70 ipm colour scanning, up to 70 ipm black and white – A4 LEF		Scan at up to 133 ipm colour scanning, up to 133 ipm black and white – A4 LEF	
<b>Resolution</b>	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)			
<b>Maximum Scan Area</b>	A3			
<b>Scan Template Management</b>	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options			
<b>Network Protocols</b>	sFTP, FTP, SMB, NetWare, HTTP, HTTPS			
<b>File Compression</b>	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A			
<b>Document Management Fields (Meta Data)</b>	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> <li>• 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations</li> <li>• Customised fields viewed on user interface for variable data input</li> </ul>			

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

<b>Scan Features</b>	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)
<b>Scan to Email (Standard)</b>	
<b>Scan Features</b>	<ul style="list-style-type: none"> <li>• Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options</li> <li>• Scan to Email S/MIME Encryption</li> <li>• Email Signing (requires Smart Card option)</li> <li>• Auto send to self</li> </ul>
<b>Directory Access</b>	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilises the Unified Address Book
<b>Scan to... (Standard)</b>	
<b>Features</b>	Scan to USB Scan to Network Folder (uses Unified Address Book entries)
<b>Network Scanning – Software Solutions</b>	
<b>Xerox® Scan to PC Desktop® Professional (Optional)</b>	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: <ul style="list-style-type: none"> <li>• PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> <li>– Complete PDF functionality</li> <li>– Secure PDF workflow of all scanning applications</li> </ul> </li> <li>• OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul>
<b>Xerox® ConnectKey® for DocuShare® (optional)</b>	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.
<b>Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer via USB from the front panel or Xerox® CentreWare® Internet Services.
<b>Security</b>	
<b>Features</b>	<ul style="list-style-type: none"> <li>• Expanded Authentication <ul style="list-style-type: none"> <li>– Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication</li> <li>– Local Authentication (internal database)</li> <li>– Smart Card authentication - 144k CAC / PIV Card Support (2048 bit certificate key) / .NET</li> </ul> </li> <li>• Secure Data <ul style="list-style-type: none"> <li>– Digitally signed PDF (when using Smart Card authentication)</li> <li>– Encrypted Scan to Email</li> <li>– Encrypted Password Protected PDF (when using Email and Network Scan Templates only)</li> <li>– Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>– Immediate Image Overwrite / Securely delete jobs using approved algorithms</li> <li>– On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>– FIPS 140-2 256 bit Hard Disk Encryption</li> </ul> </li> <li>• Expanded Authorisation <ul style="list-style-type: none"> <li>– SA access based on network credentials</li> <li>– Authorisation per user per service</li> <li>– User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> </ul> </li> <li>• Secure Network Access</li> <li>• IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec Identity Services Engine (ISE) integration, Device Security <ul style="list-style-type: none"> <li>– McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)</li> </ul> </li> <li>• Common Criteria Certification ISO 15408 (undergoing evaluation)</li> </ul>
<b>Xerox® PrintSafe Software (Optional)</b>	This authentication software integrates with trusted industry cards and readers and provides PIN access to any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.
<b>Fax</b>	
<b>Network Server Fax Features</b>	
<b>Compatibility</b>	ITU (CCITT) group 3 Various Xerox Alliance Partner Solutions
<b>Maximum Scan Area</b>	A3
<b>Fax Send Features</b>	One- or Two-sided Scanning (up to A3) Add to Send List (50 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)
<b>Fax Print Features</b>	One- or Two-sided Printing, Staple, Secure Print
<b>Transmission Resolution</b>	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

Internet Fax Features	
<b>Capability</b>	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
<b>Directory Access</b>	Utilises the Unified Address Book
<b>Send / Receive</b>	Multi-page TIFF, Image only PDF
<b>Resolution</b>	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)
<b>Network Protocols</b>	SMTP (send), POP3 (receive)
<b>Compliance</b>	ITU-T T.37 compliant
Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines)	
<b>Compatibility</b>	ITU (CCITT) Group 3
<b>Speed / Modems</b>	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilising T38 (optional)
<b>Compression / Speed</b>	MH/G3, MMR/SG3
<b>Resolution</b>	<b>Walkup Send:</b> Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi <b>Receive:</b> Accepts all sizes
<b>Fax Send Features</b>	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
<b>Fax Receive Features</b>	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
<b>Fax Forward</b>	Forward to Email or SMB Location Fax Forward on Receive Only
<b>Fax Reports</b>	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
<b>Directory Access</b>	Utilises the Unified Address Book Group fax available
<b>Auto Redial</b>	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
<b>Auto Resend</b>	Up to 5 attempts
Device Management	
<b>Management Support</b>	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
<b>Xerox® CentreWare® Web</b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> <li>• Works with any SNMP-managed printer from any manufacturer.</li> <li>• Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>• Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher.</li> <li>• CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®</li> </ul>
<b>Novell NDPS/NEPS</b>	Server gateway application: centralised management tool.
<b>Xerox® Device Manager</b>	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback and billing capabilities</li> </ul>
<b>Xerox® Device Types for SAP Environment</b>	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>
<b>Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)</b>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>



# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

<b>Xerox® Barcode Pro PS (optional)</b>	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>
<b>CentreWare Internet Services – Integrated Web Pages Provided by the Device</b>	
<b>Device Status</b>	Web server embedded in Network Server: <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul> Remote Control Panel
<b>Job Submission</b>	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS®, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
<b>Support</b>	Install print / scan drivers and online support available via web page
<b>Languages Supported</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese, Arabic
<b>Remote Print Services</b>	
<b>Automatic Meter Reading (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replacement (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).
<b>Accounting</b>	
<b>Xerox® Standard Accounting (Standard)</b>	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>• Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>
<b>Accounting Options – Network Accounting (Allows central server to manage all accounting)</b>	
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up to the minute data on how the system is being used</li> <li>• Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements with the addition of HTTPS protocol support</li> <li>• Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>• Interface with third party accounting terminal for accounting user interface</li> </ul>
<b>EFI™ Fiery® Network Server (Optional)</b>	
<b>Processor</b>	2.9 GHz, Intel® Pentium® G850 Dual-Core
<b>Memory (ESS)</b>	1 GB
<b>System Disk</b>	500 GB HDD
<b>Print Languages (PDL)</b>	PostScript v 3020
<b>Features</b>	Fiery Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Colour Tables Expert Colour Settings: Profile, Rendering and Simulation Fiery FreeForm – Variable Data capabilities Booklet Maker 4.0 – booklet wizard to create booklets Print from USB flash drive Secure Erase EFI PrintMe Fiery® VUE Calibration Secure Printing User Authentication Drag and Drop job Management with CWS Importing Jobs
<b>Connectivity</b>	10Base-T/100Base-TX/1000Base-T Ethernet
<b>Optional</b>	Fiery Options Bundle (Spot-On, Auto Trapping, Hot folders, Virtual Printers) Network Switch to connect both printer and Fiery Server to Network

# Xerox® WorkCentre® 7830i/7835i/7845i/7855i

Supplies			
<b>Toner Cartridges (Sold)<sup>5</sup></b>	Black	26,000 pages	006R01513
	Cyan	15,000 pages	006R01516
	Magenta	15,000 pages	006R01515
	Yellow	15,000 pages	006R01514
<b>Transfer Belt Cleaner</b>	1 Assembly	160,000 pages	001R00613
<b>Second Bias Transfer Roll</b>	1 Assembly	200,000 pages	008R13064
<b>Staple Cartridges</b>	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925
<b>Staple Refills</b>	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
<b>Xerox® Smart Kit®</b>			
<b>Drum Cartridge<sup>6</sup></b>	1 Cartridge per Colour	125,000	013R00662
<b>Waste Toner Container<sup>7</sup></b>	1 Cartridge	43,000	008R13061

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput

<sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> XPS option is required to print XPS files.

<sup>5</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

<sup>6</sup> Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 30% colour / 70% black and white pages.

<sup>7</sup> Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

For more information, visit us at [www.xerox.com/office](http://www.xerox.com/office)

©2016 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, Scan to PC Desktop®, SmartKit®, SuppliesAssistant® and WorkCentre® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 09/16 BR9497 W7855-01EI

