



## Lexmark CS730de

Colour and performance



# Lexmark CS730de

Designed for security, ease of use, and sustainability, the Lexmark CS730de delivers professional colour for mid-to-large workgroups at speeds up to 40 pages per minute\*. The 10.9 cm tablet-like touchscreen makes completing your printing tasks intuitively easy. Replacement cartridges with Unison™ Toner yield up to 22,000/10,500 black/colour pages\*\* to keep you going.

## Robust, enduring quality

- ▶ Enjoy high-quality colour output in a wide variety of environments - from back-office to retail to harsh manufacturing conditions.
- ▶ Intentionally engineered to last seven years or more with durable steel frames and long-life components.
- ▶ Unison™ Toner replacement cartridges yield up to 22,000/10,500 black/colour pages\*\*.



## Always easy. Always intuitive.

- ▶ Powerful features are easy to use.
- ▶ Large, tablet-like, button-free touchscreens help you intuitively complete every task, from the basic to the complex.
- ▶ Add Lexmark or third-party apps to meet your specific business needs.

## Make a statement with professional colour

- ▶ Enjoy the benefits of vibrant, professional-quality output allowing you to do more colour printing in-house - saves time and money.

- ▶ Match corporate colours on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Colour Replacement.

## Secure by design

- ▶ Lexmark security features help keep your information safe - in the document, on the device, over the network and at all points in between.
- ▶ Always improving security, we now include a standard Trusted Platform Module\*\*\*, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

## Sustainability matters

- ▶ Designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

## Power up with IoT

- ▶ Our sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.


This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark CS730de



- 1

**Printer with 10.9 cm touch screen**  
413 x 479 x 489 mm
- 2

**550-Sheet tray with 100-sheet multipurpose feeder**  
Dimensions included as part of base model
- 3

**550-Sheet Drawer (incl. Tray)**  
119 x 463 x 483 mm
- 4

**550-Sheet Drawer (incl. Tray)**  
119 x 463 x 483 mm
- 5

**550-Sheet Drawer (incl. Tray)**  
119 x 463 x 483 mm
- 6

**550-Sheet Drawer (incl. Tray)**  
119 x 463 x 483 mm
- 7

**Printer Stand (adjustable height)**  
521 x 653 x 625 mm
- Standard

Optional

<b>P/N</b>	<b>Hardware</b>
47C9020	Lexmark CS730de
<b>P/N</b>	<b>Supplies</b>
71C0H10	Lexmark CS730, 735, CX730 Black 22K Toner Cartridge
71C0H20	Lexmark CS/CX730 Cyan 10.5K Toner Cartridge
71C0H30	Lexmark CS/CX730 Magenta 10.5K Toner Cartridge
71C0H40	Lexmark CS/CX730 Yellow 10.5K Toner Cartridge
71C0W00	Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container
71C0Z10	Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit
71C0Z50	Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit
71C20C0	Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge
71C20K0	Lexmark CS/CX730, 735 Black Return Programme 5K Toner Cartridge
71C20M0	Lexmark CS/CX730, 735 Magenta Return Programme 5K Toner Cartridge
71C20Y0	Lexmark CS/CX730, 735 Yellow Return Programme 5K Toner Cartridge
71C2HC0	Lexmark CS/CX730 Cyan Return Programme 10.5K Toner Cartridge
71C2HK0	Lexmark CS730, 735, CX730 Black Return Programme 22K Toner Cartridge
71C2HM0	Lexmark CS/CX730 Magenta Return Programme 10.5K Toner Cartridge
71C2HY0	Lexmark CS/CX730 Yellow Return Programme 10.5K Toner Cartridge

<b>P/N</b>	<b>Paper Handling</b>
40C2100	CS72x, CX725 550-Sheet Drawer (incl. Tray)
<b>P/N</b>	<b>Memory Options</b>
27X0400	500+ GB Hard Disk
57X9528	Intelligent Storage Drive (ISD)

<b>P/N</b>	<b>Application Solutions</b>
57X0300	Contact Authentication Device
57X0301	Contactless Authentication Device
82S1203	IPDS License
82S1204	Bar Code License

<b>P/N</b>	<b>Connectivity</b>
1021294	USB Cable (2 meter)
27X0823	MarkNet N8370 Wireless for CS720, CS725, CX725
27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
SPD0002	Surge protective device

<b>P/N</b>	<b>Furniture</b>
40C2300	CS72x, CX725 Printer Stand (adjustable height)

Supports up to four optional 550-sheet trays.  
All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at [http://www.lexmark.com/publications/furniture\\_safety/](http://www.lexmark.com/publications/furniture_safety/)  
IPDS License and Bar Code License require an Intelligent Storage Drive.

Product Specifications		Lexmark CS730de
Printing		
Display	Lexmark e-Task 10,9 cm colour touch screen with audible feedback	
Print speed	up to: black: 40 ppm <sup>1</sup> (A4) / colour: 40 ppm <sup>1</sup> (A4)	
Time to first page	as fast as: black: 6.4 seconds / colour: 7.0 seconds	
Print resolution	black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / colour: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi	
Memory	standard: 1024 MB / maximum: 1024 MB	
Hard Disk	Intelligent Storage Drive (optional); Magnetic Hard Disk (optional)	
Recommended monthly page volume	1500 - 15000 pages <sup>2</sup>	
Maximum monthly duty cycle	up to: 120000 pages per month <sup>3</sup>	
Supplies <sup>4</sup>		
Cartridge yields	up to: 10,500 <sup>5</sup> -page Colour (CMY) High Yield Cartridges / up to: 22,000 <sup>5</sup> -page Black High Yield Cartridge	
Imaging unit yield	up to: 150000 pages, based on average 3 pages per print job and 5% coverage <sup>6</sup>	
Cartridge(s) shipped with product	5,000 <sup>5</sup> -page Black and Colour (CMYK) Return Programme Toner Cartridges <sup>5</sup>	
Paper Handling		
Standard paper handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-sheet output bin, 550-Sheet Input	
Optional paper handling	550-Sheet Tray	
Paper input capacity	up to: standard: 650 pages / maximum: 2850 pages	
Paper output capacity	up to: standard: 300 pages / maximum: 300 pages	
Media types supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide	
Media sizes supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope	
General Information <sup>7</sup>		
Standard connectivity	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port (compatible with USB 2.0 specification, type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot	
Optional network ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC	
Noise Level	Operating: 52 dBA (Print)	
Specified operating environment	Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity	
Product guarantee	1-Year Onsite Repair, Next Business Day	
Size / Weight	HxWxD: 413 x 479 x 489 mm / 32 kg	
Energy Star Typical Electricity Consumption	TEC: 0.53 kWh per week	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. <sup>6</sup> Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>7</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

